

TDLT系列三回程烘干系统

TDLT Series Triple-pass Drying System

系统简介 Brief Introduction

TDLT三回程烘干系统是在S62系列基础上研发的第三代三回程烘干机，它占地面积小、处理量大、热利用率高。经过不断改进，现已达到国际先进水平，能高效地处理粘性较低的高水分物料、颗粒状物料以及沙子、矿石、矿粉、果渣、药渣等。

TDLT triple-pass drying system is the third generation triple-pass dryer developed from S62 series drying machine. It is characterized by small occupation area, large handling capacity and high thermal efficiency. After continuous improvement, TDLT drying system has reached to international advanced level. It can be used to efficiently deal with materials with low viscosity and high moisture content, particles materials and other special materials such as sand, mineral ore, mineral powder, pomace and medicine dregs.



主要技术参数

Technical Parameters

| 设备规格 Specifications | 产量(t/h) Capacity | | | | 功率 Power(kw) |
|------------------------|------------------|-------------|---------|---------|-----------------|
| | 矿渣 Slag | 粉煤灰 Fly Ash | 粘土 Clay | 黄沙 Sand | |
| TDLT320.4 | 5~10 | 4 | 4~6 | 10~15 | 11 |
| TDLT320.5 | 10~15 | 6 | 6~8 | 15~20 | 11 |
| TDLT325.5 | 20~25 | 8 | 8~12 | 20~25 | 15 |
| TDLT325.6 | 25~30 | 10 | 12~15 | 25~30 | 15 |
| TDLT328.6 | 30~35 | 15 | 15~20 | 35~40 | 22 |
| TDLT330.6 | 35~40 | 20 | 20~25 | 40~45 | 30 |
| TDLT330.7 | 40~45 | 25 | 25~30 | 45~50 | 30 |
| TDLT332.7 | 45~50 | 30 | 30~35 | 50~60 | 44 |
| TDLT332.8 | 50~60 | 35~40 | 35~40 | 60~70 | 44 |
| TDLT336.8 | 60~70 | 40~45 | 40~45 | 70~80 | 60 |
| TDLT338.9 | 70~80 | 45~50 | 45~50 | 80~90 | 60 |
| TDLT34.10 | 80~90 | 50~60 | 50~60 | 90~100 | 74 |